

Script HW/SW AIX

Article Number: 218 | Rating: Unrated | Last Updated: Mon, Jun 4, 2018 2:02 PM

####

```
pwd;
clear;
SERVER=`hostname`  
sleep 2;  
>/tmp/${SERVER};  
echo "#####" >> /tmp/${SERVER};  
echo "DATE: " >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
date >> /tmp/${SERVER};  
/nas/install/scripts/disk_size.sh >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
echo "HOSTNAME: " >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
hostname >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
echo "NETWORK: " >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
ifconfig -a >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
for i in `lsdev -Cc adapter | grep "ent" | awk '{ print $1 }'` ; do echo ${i} ; done >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
echo "LAN ATTR: " >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
for i in `lsdev -Cc adapter | grep "ent" | awk '{ print $1 }' | tr -d 't'` ; do echo "####" ; lsattr -EHI ${i} ;  
echo "####" ; done >> /tmp/${SERVER};  
for i in `lsdev -Cc adapter | grep "ent" | awk '{ print $1 }'` ; do echo "####" ; lsattr -EHI ${i} ; echo  
"####" ;done >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
echo "VLANS: " >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
for i in `lsdev -Cc adapter | grep "ent" | awk '{ print $1 }'` ; do entstat -d ${i} | grep 'Port VLAN ID';
```

```

done >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
echo "ROUTING: " >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
netstat -nr >> /tmp/${SERVER};
netstat -in >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
echo "VPD Network " >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
for i in `lsdev -Cc adapter | grep "^ent" | awk '{ print $1 }'` ; do echo "#####"; lscfg -vpl ${i}; echo "#####"; done >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
echo "ARP: " >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
arp -a | grep "at" >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
echo "FC: " >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
for i in `lsdev -Cc adapter | grep "^fcs" | awk '{ print $1 }'` ; do echo ${i} ; done >> /tmp/${SERVER};
for i in `lsdev -Cc adapter | grep "^fcs" | awk '{ print $1 }'` ; do fcstat ${i} ; done >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
echo "FC ATTR: " >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
for i in `lsdev -Cc adapter | grep "^fcs" | awk '{ print $1 }'` ; do echo "#####"; lsattr -EHI ${i} ; echo "#####"; done >> /tmp/${SERVER};
for i in `lsdev -Cc adapter | grep "^fcs" | awk '{ print $1 }' | tr -d 'fcs'` ; do echo "#####"; lsattr -EHI fscsi${i} ; echo "#####"; done >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
echo "VPD FC: " >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
for i in `lsdev -Cc adapter | grep "^fcs" | awk '{ print $1 }'` ; do echo "#####"; lscfg -vpl ${i} | grep "Network Address"; echo "#####"; done >> /tmp/${SERVER};
for i in `lsdev -Cc adapter | grep "^fcs" | awk '{ print $1 }'` ; do echo "#####"; lscfg -vpl ${i} ; echo "#####"; done >> /tmp/${SERVER};
for i in `lsdev -Cc adapter | grep "^fcs" | awk '{ print $1 }'` ; do echo "#####"; fcstat ${i} ; echo "#####"; done >> /tmp/${SERVER};
echo "-----" >> /tmp/${SERVER};
echo "LSPATH FC: " >> /tmp/${SERVER};

```

```
echo "-----" >> /tmp/${SERVER};  
lspath -F "name:connection:parent:path_status:status:path_id" >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
echo "LSMPIO: " >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
lsmpio >> /tmp/${SERVER};  
echo "-----" >> /tmp/${SERVER};  
echo "#####" >> /tmp/${SERVER};  
pwd;  
cat /tmp/${SERVER};  
  
####
```

Posted - Mon, Jun 4, 2018 2:02 PM. This article has been viewed 9065 times.

Online URL: <http://kb.ictbanking.net/article.php?id=218>