

To do a quick check on the number of path present (does not mean all are Enabled] using for loop

Article Number: 234 | Rating: Unrated | Last Updated: Fri, Jun 8, 2018 9:32 PM

To do a quick check on the number of path present (does not mean all are Enabled] using for loop.

=====

```
for i in `usr/sbin/lspath | grep scsi | awk '{print $2}' | sort | uniq ` ; do echo "$i `usr/sbin/lspath | awk '/$i' / | uniq | awk '/Enabled/' | wc -l`" ; done
```

```
for i in `usr/sbin/lspath | grep scsi | awk '{print $2}' | sort | uniq ` ; do echo "$i `usr/sbin/lspath | awk '/$i' / {print $2}' | wc -l`" ; done
```

```
hdisk0      2
hdisk1      2
hdisk2      2
hdisk3      2
hdisk4      2
```

=====

The below command will use lspath to identify number of path configured and number of those path which are online

=====

```
echo "Dev      NoPath  Online  ThroughNoOfInterface" ; for i in `lspath -H -F 'name parent path_id connection status' | awk '!/name / {print $1}' | sort | uniq ` ; do echo "$i; `lspath -H -F 'name parent path_id connection status' | awk '/$i' /{print $4}' | uniq | wc -l`; `lspath -H -F 'name parent path_id connection status' | awk '/$i' / && /Enabled/ {print $4}' | uniq | wc -l`;      `lspath -H -F 'name parent
```

```
path_id connection status' | awk '/$i' / {print $2}' | uniq | wc -l`" ; done
```

Dev	NoPath	Online	ThroughNoOfInterface
hdisk0;	1;	1	1
hdisk1;	1;	1	1
hdisk2;	3;	1	1
hdisk3;	3;	1	1
hdisk4;	3;	1	1

=====

Posted - Fri, Jun 8, 2018 9:30 PM. This article has been viewed 4095 times.

Online URL: <http://kb.ictbanking.net/article.php?id=234>