

AIX: Script to create a file with commands to remove missing & failed paths

Article Number: 262 | Rating: 5/5 from 1 votes | Last Updated: Tue, Jun 12, 2018 9:02 AM

[To create a file with commands to remove the missing paths](#)

```
1
2                                     #!/bin/sh
3
4                                     # rmpaths
5
6                                     >xrmpaths
7
8                                     echo "#!/bin/sh" >>xrmpaths
9
10                                    disks=$(lspv | awk '{print $1}')
11
12                                    for loop in $disks
13
14                                    do
15
16                                    lspath -l $loop -H -F
17                                    "name:parent:connection:status" |grep Missing| awk
18                                    -F: '{print "rmpath -dl",$1,"-p", $2, "-w",
19                                    $3}'>>xrmpaths
20
21                                    done
```

To create a file with commands to remove the failed paths

```
1                               #!/bin/sh
2
3                               # rmpaths
4
5                               >xrmpaths
6
7                               echo "#!/bin/sh" >>xrmpaths
8
9                               disks=$(lspv | awk '{print $1}')
10
11                              for loop in $disks
12
13                              do
14
15                              lspath -l $loop -H -F
16                              "name:parent:connection:status" |grep Failed| awk
17                              -F: '{print "rmpath -dl",$1,"-p", $2, "-w",
18                              $3}'>>xrmpaths
19
20                              done
```

Posted - Tue, Jun 12, 2018 9:02 AM. This article has been viewed 3384 times.

Online URL: <http://kb.ictbanking.net/article.php?id=262>