

watchdog How to restart a process out of crontab on a Linux/Unix

Article Number: 343 | Rating: Unrated | Last Updated: Tue, Jul 31, 2018 9:30 AM

How to restart a process out of crontab on a Linux/Unix

last updated December 25, 2017 in Categories [CentOS](#), [Debian / Ubuntu](#), [FreeBSD](#), [Linux](#), [Suse](#), [UNIX](#)



I am a new Linux user and not familiar with crontab syntax. How do I use a cron job to restart server process if not running on a Linux or Unix-like system?

There are many ways to make sure that the essential server process such as HTTPD/Nginx/PHP-FPM/MySQL remains up and running all the time.



How To Use a Simple Bash Script And Cronjob To Restart Server Programs

This tutorial shows how to create and use a simple bash shell script to restart failed services using crontab.

Step 1 – Create a Bash Shell Script

Here [is a simple shell script to check for httpd pid using](#) the pgrep command. It will restart if httpd is not running on a CentOS/RHEL using the systemctl command. Create a file named /root/bin/restart-httpd
vi /root/bin/restart-httpd

Append the following code:

Posted - Tue, Jul 31, 2018 9:30 AM. This article has been viewed 6251 times.

Online URL: <http://kb.ictbanking.net/article.php?id=343>