Reconfigure RSCT ID to fix DLPAR issues on cloned AIX systems

Article Number: 523 | Rating: 5/5 from 1 votes | Last Updated: Thu, Feb 21, 2019 8:29 PM ON AIX systems, RMC daemons are part of the Reliable, Scalable Cluster Technology (RSCT). They allows the HMC to communicate with a managed logical partition to do DLPAR operations. But, when we clone an AIX system, for example using mksysb, RSCT ID is not reconfigured and of course, DLPAR is not working anymor.

To solve this issue, you need to reconfigure RSCT ID. FOllwo this steps to fix this issue.

1- Get RSCT ID (before change it).

2- Reconfigure RSCT ID on AIX client.

[root@aix:/] /usr/sbin/rsct/install/bin/uncfgct -n

[root@aix:/] /usr/sbin/rsct/install/bin/cfgct

[root@aix:/] /usr/sbin/rsct/install/bin/cfgct

3- Verify RSCT ID (after change it)

```
[root@aix:/] cat /etc/ct_node_id

bfcc4535bc55378
```

4- Restart RMC on AIX client.

```
[root@aix:/] /usr/sbin/rsct/bin/rmcctrl -z

[root@aix:/] /usr/sbin/rsct/bin/rmcctrl -A

[root@aix:/] /usr/sbin/rsct/bin/rmcctrl -p
```

- 5- Wait 5 min and check again RMC connection between HMC or FSM.
- 5- From AIX, check conenction wirh HMC/FSM.

```
[root@aix:/] -> lsrsrc IBM.MCP

Resource Persistent Attributes for IBM.MCP

resource 1:

MNName = "172.16.yyy.xxx" <----
AIX client IP
```

```
NodeID
                                                           = 4273918179149062022
                                              KeyToken = "FSMPureflex" <----
                                          HSM/FSM HOSTNAME
                                              IPAddresses = {"172.21.yyy.xxx"} < ----
                                          HSM/FSM IP
10
                                              ConnectivityNames = {"172.16.yyy.xxx"}
                                          <---- AIX client IP
11
                                              HMCName = "7955-01M*13FFFBB"
12
                                              HMCIPAddr
                                                              = "172.21.yyy.xxx" <----
13
                                          HSM/FSM IP
14
                                              HMCAddIPs = "172.21.yyy.xxx" <----
                                          HSM/FSM IP
                                              HMCAddIPv6s = "fd0a:bb18:7987:0:42f2:
                                          e9ff:fe58:46ba,fe80::42f2:e9ff:fe58:46ba,fd79:32b
                                          2:e57:0:42f2:e9ff:fe58:46bb,fe80::42f2:e9ff:fe58:4
                                          6bb"
                                              ActivePeerDomain = ""
                                              NodeNameList = {"aix_hostname"}
```

Posted - Thu, Feb 21, 2019 8:29 PM. This article has been viewed 13744 times.

Online URL: http://kb.ictbanking.net/article.php?id=523