

Changing Ethernet Media Speed for AIX

Article Number: 549 | Rating: Unrated | Last Updated: Tue, Apr 16, 2019 5:50 PM

First you need to find out the device name of your ethernet card. It should be ent0 if the machine has only 1 ethernet card. Otherwise, it may be a higher number.

You can determine the legal values for the media speed of the card by running the following command (where the value of ent0 may be different if you machine has multiple ethernet cards).

```
lsattr -R -l ent0 -a media_speed
```

If this command results in the following error—

```
lsattr: 0514-528 The "media_speed" attribute does not exist in the predefined device configuration database.
```

—then the ethernet card is a 10Mbps card that will only do 10Mbps/half duplex

If you do have a 100Mbps card, the lsattr command will return something like this:

```
10_Half_Duplex
10_Full_Duplex
100_Half_Duplex
100_Full_Duplex
Auto_Negotiation
```

These are the media speeds the card will understand. To see the cards current media speed setting you can run

```
lsattr -EH -l ent0 -a media_speed
```

To change the media speed, run:

```
chdev -P -l ent0 -a media_speed=100_Half_Duplex
```

The value for media_speed can be any of the values listed by the lsattr -R command above. The change does not take effect until you reboot the machine.

If you select a value other than Auto_Negotiation the switch port the machine is connected to must have the same configuration. If the switch and the machine do not match you may get no network connectivity or poor performance.

Posted - Tue, Apr 16, 2019 5:50 PM. This article has been viewed 3327 times.

Online URL: <http://kb.ictbanking.net/article.php?id=549>