

AIX lspath Missing path

Article Number: 407 | Rating: Unrated | Last Updated: Fri, Oct 5, 2018 12:04 PM

Reviewing disk paths, I found some paths showing as Missing and some enabled on the same fscsi

```
root@aix:/ # lspath -l hdisk31
Enabled hdisk31 fscsi0
Missing hdisk31 fscsi0
Enabled hdisk31 fscsi0
Missing hdisk31 fscsi0
Enabled hdisk31 fscsi2
Missing hdisk31 fscsi2
Enabled hdisk31 fscsi2
Missing hdisk31 fscsi2
```

To correct this situation we will remove the path and recognize again. Check if there is a disk with only one path

```
root@aix:/ # lspath
```

Remove one path, run cfgmgr. Remove the other one and run cfgmgr

```
root@aix:/ # rmpath -p fscsi2 -d
root@aix:/ # cfgmgr
root@aix:/ # rmpath -p fscsi0 -d
root@aix:/ # cfgmgr
```

It should display like this

```
root@aix:/ # lspath -l hdisk31  
Enabled hdisk31 fscsi0  
Enabled hdisk31 fscsi0  
Enabled hdisk31 fscsi2  
Enabled hdisk31 fscsi2
```

Posted - Fri, Oct 5, 2018 12:04 PM. This article has been viewed 11403 times.

Online URL: <http://kb.ictbanking.net/article.php?id=407>